

LED LIGHTING SYSTEM



PREMISES OF MEAT INDUSTRY



THE LIGHTING SYSTEM PROVIDES:

- Highly efficient LED with lifetime >50,000 hours - Long Lifetime;
- IP67 watertight and dust-proof: this pig farm lighting can be used in a bad environment;
- Against cleaning chemicals and ammonia gas resistance;
- Flicker free;
- Mounted junction box IP66/ IP68.

SPECIFICATIONS OF THE LIGHTING SYSTEM:

	Voltage, B	220 B AC
	Range dimmer	0 - 100%
	Protection class	II+, III
	Operating temperature , °C	-10...+50
	IP Grade	IP66/IP68
	Service life , not less than years	8



TECHNICAL CHARACTERISTICS OF LAMP:

MODEL	POWER, W	VOLTAGE, U	TUBE	LIGHT OUTPUT, LM	CTT, K	IP GRADE	CRI	DIAMETR	LENGHT
GL220-A-018.0XX-021*	18	220	TRANSPARENT MATTE	<u>2000</u> 1700	3000 / 4000 / 5000	Ip67	>80	30 mm	1080 mm
GL220-A-024.0XX-021*	24	220	TRANSPARENT MATTE	<u>2600</u> 2210	3000 / 4000 / 5000	Ip67	>80	30 mm	1080 mm
GL220-A-016.0XX-422*	16	220	TRANSPARENT MATTE	<u>2400</u> 2040	3000 / 4000 / 5000	Ip67	>80	34 mm	720 mm
GL220-A-032.0XX-442*	32	220	TRANSPARENT MATTE	<u>4800</u> 4080	3000 / 4000 / 5000	Ip67	>80	34 mm	1340 mm
GL220-A-040.0XX-733*	40	220	TRANSPARENT MATTE	<u>6000</u> 5100	3000 / 4000 / 5000	Ip67	>80	34 mm	1590 mm
GL220-A-050.0XX-743*	50	220	TRANSPARENT MATTE	<u>7500</u> 6375	3000 / 4000 / 5000	Ip67	>80	34 mm	2060 mm
GL220-A-018.0XX-422*	18	220	TRANSPARENT MATTE	<u>2700</u> 2300	3000 / 4000 / 5000	Ip67	>80	30 mm	790 mm
GL220-A-022.0XX-432*	22	220	TRANSPARENT MATTE	<u>3300</u> 2800	3000 / 4000 / 5000	Ip67	>80	30 mm	1100 mm
GL220-A-030.0XX-442*	30	220	TRANSPARENT MATTE	<u>4500</u> 2930	3000 / 4000 / 5000	Ip67	>80	30 mm	1410 mm

* Red/white (also available in blue, red or green)



308009, Russia, Belgorod,
Rabochaya St. 12, building E, office 201



+7 (4722) 200-853



info@gelan.su